

# peroxy::lyser

## for drinking water

peroxy::lyser monitors peracetic acid (PAA)

- s::can plug & measure
- measuring principle: amperometric (membrane covered)
- ideal for all kinds of water treatment
- long term stable and lowest maintenance in operation
- replacement of membrane only once a year
- readings stable even at high fluctuations of pH, temperature and flow
- strong surfactants are tolerated
- not cross sensitive to high concentrations of hydrogen peroxide
- factory precalibrated
- mounting and measurement in a flow cell
- operation via s::can terminals & s::can software
- additionally also measures temperature

### recommended accessories

part number	article name
D-330-xxx	con::cube V3
D-320-xxx	con::lyte
C-1-010-sensor	1 m connection cable for s::can physical and ISE probes
F-45-four	flow cell for four s::can physical probes
F-45-sensor	flow cell for s::can sensor
S-11-xx-moni	moni::tool Software
E-515-1/2-SET	Peracetic Acid membrane cap (spare part)
E-515-1/2-EL	Peracetic Acid electrolyte (spare part)



**technical specification**

measuring principle	amperometric	housing material	PVC
measuring principle detail	potentiostatic 2-electrode system, membrane covered		Stainless steel 1.4571
resolution	0.1 mg/l for 0 - 200 mg/l 1 mg/l for 0 - 2000 mg/l		150 g
automatic compensation instrument	temperature	dimensions (Ø x l)	35 x 208 mm
response time (T90)	1.5 ... 5 min.	operating temperature	0 ... 45 °C
integration via	con::lyte con::nect	operating pressure	0 ... 1 bar
power supply	9 ... 30 VDC	installation / mounting	flow cell
power consumption (typical)	0.5 W	process connection	quick connect
power consumption (max.)	0.6 W	recommended flow	15 ... 30 l/h (in s::can flow cell)
interface to s::can terminals	sys plug (IP67), RS485	pH range	1 ... 6
		storage temperature	0 ... 45 °C
		conformity - EMC	EN 61326-1
		protection class (-000)	IP67

**measuring range**

		parameter		
peroxy::lyser	min.	PAA [mg/l]	temperature [°C]	part number
	max.	0	0	
peroxy::lyser	min.	200	45	E-515-1-000
	max.	0	0	
		2000	45	E-515-2-000